

WATER SPRINT RACE

2023





Profine® lilac

Temporary hardness reduction
and microfiltration



18° f (10° dh) inlet

CHARACTERISTICS:

- removes odour and off-taste
- reduces chlorine
- guarantees a bacteriostatic action
- reduces temporary hardness
- protection of plants
- efficient against limescale

APPLICATIONS



steam ovens



coffee

in brackets the value of the bypass

PROFINE	-	SMALL 700 Liters (0%)	MEDIUM 1.100 Liters (0%)	LARGE 1.600 Liters (0%)	BIG 2.0 2.500 Liters (15%)	BIG 3.0 3.750 Liters (15%)	BIG 4.5 5.625 Liters (15%)	BIG 6.0 7.500 Liters (15%)	-
BWT	-	Bestmax S 755 Liters (15%)	-	Bestmax V 1.895 Liters (15%)	Bestmax M 2.880 Liters (15%)	Bestmax L 3.945 Liters (15%)	Bestmax XL 5.155 Liters (15%)	Bestmax 2XL 9.100 Liters (15%)	-
	-	Bestmax SMART 15 1.500 Liters	Bestmax SMART 20 2.700 Liters	Bestmax SMART 25 3.800 Liters	Bestmax SMART 30 5.800 Liters	Bestmax SMART 40 9.300 Liters	Bestmax SMART 42 13.000 Liters (45%)	Bestmax SMART 45 17.000 Liters	-
	-	Bestmax SOFT S 1.200 Liters (45%)	-	Bestmax SOFT V 3.000 Liters (45%)	Bestmax SOFT M 4.560 Liters (45%)	Bestmax SOFT XL 8.160 Liters (45%)	-	Bestmax SOFT 2XL 14.400 Liters (45%)	-
PENTAIR	-	-	CLARIS-S 1.700 Liters (60%)	CLARIS-M 3.000 Liters (60%)	-	CLARIS-L 5.600 Liters (60%)	CLARIS-XL 8.000 Liters (60%)	CLARIS-XXL 13.200 Liters (60%)	-
	-	-	ESO6 1.483 Liters	ESO 7 1.917 Liters	-	-	-	-	-
	-	-	CLARIS ULTRA 170 1.500 Liters (70%)	CLARIS ULTRA 250 2.250 Liters (70%)	CLARIS ULTRA 500 3.750 Liters (70%)	CLARIS ULTRA 1000 7.000 Liters (70%)	CLARIS ULTRA 1500 10.000 Liters (70%)	CLARIS ULTRA 2000 16.500 Liters (70%)	-
BRITA	-	PURITY C Quell ST C50 600 Liters (0%)	-	PURITY C Quell ST C150 1.505 Liters (0%)	PURITY C Quell ST C300 2.500 Liters (0%)	-	PURITY C Quell ST C500 4.250 Liters (0%)	-	PURITY C Quell ST C1100 7.188 Liters (0%)
	-	-	-	-	-	-	PURITY Quell ST 450 4.217 Liters (40%)	PURITY Quell ST 600 7.207 Liters (40%)	PURITY C Quell ST 1200 13.187 Liters (40%)



Profine® *brown*

Temporary hardness reduction
and microfiltration



CHARACTERISTICS:

- removes odour and off-taste
- reduces chlorine
- guarantees a bacteriostatic action
- reduces temporary hardness
- protection of plants
- efficient against limescale

APPLICATIONS



vending

by-pass 1 (15%) and 18° f (10° dh) inlet

in brackets the value of the bypass

PROFINE	-	SMALL 875 Liters (15%)	MEDIUM 1.375 Liters (15%)	LARGE 2.000 Liters (15%)	BIG 2.0 2.500 Liters (15%)	BIG 3.0 3.750 Liters (15%)	BIG 4.5 5.625 Liters (15%)	BIG 6.0 7.500 Liters (15%)	-
BWT	-	Bestmax S 755 Liters (15%)	-	Bestmax V 1.895 Liters (15%)	Bestmax M 2.880 Liters (15%)	Bestmax L 3.945 Liters (15%)	Bestmax XL 5.155 Liters (15%)	Bestmax 2XL 9.100 Liters (15%)	-
	-	Bestmax SMART 15 1.500 Liters	Bestmax SMART 20 2.700 Liters	Bestmax SMART 25 3.800 Liters	Bestmax SMART 30 5.800 Liters	Bestmax SMART 40 9.300 Liters	Bestmax SMART 42 13.000 Liters (45%)	Bestmax SMART 45 17.000 Liters	-
	-	Bestmax SOFT S 1.200 Liters (45%)	-	Bestmax SOFT V 3.000 Liters (45%)	Bestmax SOFT M 4.560 Liters (45%)	Bestmax SOFT XL 8.160 Liters (45%)	-	Bestmax SOFT 2XL 14.400 Liters (45%)	-
PENTAIR	-	-	CLARIS-S 1.700 Liters (60%)	CLARIS-M 3.000 Liters (60%)	-	CLARIS-L 5.600 Liters (60%)	CLARIS-XL 8.000 Liters (60%)	CLARIS-XXL 13.200 Liters (60%)	-
	-	-	ESO6 1.483 Liters	ESO 7 1.917 Liters	-	-	-	-	-
	-	-	CLARIS ULTRA 170 1.500 Liters (70%)	CLARIS ULTRA 250 2.250 Liters (70%)	CLARIS ULTRA 500 3.750 Liters (70%)	CLARIS ULTRA 1000 7.000 Liters (70%)	CLARIS ULTRA 1500 10.000 Liters (70%)	CLARIS ULTRA 2000 16.500 Liters (70%)	-
BRITA	-	PURITY C Quell ST C50 600 Liters (0%)	-	PURITY C Quell ST C150 1.505 Liters (0%)	PURITY C Quell ST C300 2.500 Liters (0%)	-	PURITY C Quell ST C500 4.250 Liters (0%)	-	PURITY C Quell ST C1100 7.188 Liters (0%)
	-	-	-	-	-	-	PURITY Quell ST 450 4.217 Liters (40%)	PURITY Quell ST 600 7.207 Liters (40%)	PURITY C Quell ST 1200 13.187 Liters (40%)



Profine® violet

Temporary hardness
reduction with pH control



18° f (10° dh) inlet

CHARACTERISTICS:

- removes odour and off-taste
- reduces chlorine
- guarantees a bacteriostatic action
- pH stable
- reduces temporary hardness
- protection of plants
- efficient against limescale

APPLICATIONS



steam ovens



coffee

PROFINE	-	SMALL 700 Liters	MEDIUM 1.100 Liters	LARGE 1.600 Liters	BIG 2.0 2.000 Liters	BIG 3.0 3.000 Liters	BIG 4.5 4.500 Liters	BIG 6.0 6.000 Liters	-
BWT	-	Bestprotect S 600 Liters	-	Bestprotect V 1.500 Liters	-	-	Bestprotect XL 3.590 Liters	Bestprotect 2XL 6.000 Liters	-



Profine® *cream*

Temporary hardness
reduction with pH control



18° f (10° dh) inlet

CHARACTERISTICS:

- removes odour and off-taste
- reduces chlorine
- guarantees a bacteriostatic action
- pH stable
- reduces temporary hardness
- protection of plants
- efficient against limescale

APPLICATIONS



vending

<u>PROFINE</u>	-	SMALL 700 Liters	MEDIUM 1.100 Liters	LARGE 1.600 Liters	BIG 2.0 2.000 Liters	BIG 3.0 3.000 Liters	BIG 4.5 4.500 Liters	BIG 6.0 6.000 Liters	-
<u>BWT</u>	-	Bestprotect S 600 Liters	-	Bestprotect V 1.500 Liters	-	-	Bestprotect XL 3.590 Liters	Bestprotect 2XL 6.000 Liters	-



Profine® ocra

Total hardness reduction
and microfiltration



by-pass 1 (25%) and 18° f (10° dh) inlet

CHARACTERISTICS:

- removes odour and off-taste
- reduces chlorine
- guarantees a bacteriostatic action
- reduces total hardness
- protection of plants
- efficient against limescale

APPLICATIONS



steam ovens



coffee

in brackets the value of the bypass

PROFINE	-	SMALL 710 Liters	MEDIUM 1.150 Liters	LARGE 1.680 Liters	BIG 2.0 1.780 Liters (25%)	BIG 3.0 2.670 Liters (25%)	BIG 4.5 4.000 Liters (25%)	BIG 6.0 5.330 Liters (25%)	-
BRITA	-	-	PURITY C FINEST C150 1.100 Liters	-	-	PURITY C FINEST C300 1.800 Liters	PURITY C FINEST C500 3.414 Liters	PURITY FINEST 600 4.400 Liters	PURITY C FINEST C1100 6.000 Liters



Profine® red

Prefiltration in systems
of water treatment



CHARACTERISTICS:

- stop dirt and sand
- reduces water turbidity
- efficient by itself or as pre-treatment

APPLICATIONS



domestic

<u>PROFINE</u>	-	SMALL 5 µm clogging (2.5 bar)	MEDIUM 5 µm clogging (2.5 bar)	LARGE 5 µm clogging (2.5 bar)	-	-	-	-	-
<u>PENTAIR</u>	-	EC110 10 µm	-	EC210 10 µm	-	-	-	-	-



Profine® blue

Drinking water
dechlorination and clarification



CHARACTERISTICS:

- removes odours and off-tastes
- reduces chlorine
- reduces water turbidity
- reduces the organic macromolecules presence

APPLICATIONS



domestic



coffee



professional
washing

PROFINE	-	SMALL 15.000 Liters	MEDIUM 24.000 Liters	LARGE 45.000 Liters	-	-	-	-	-
PENTAIR	S-100 5.670 Liters	-	-	-	-	-	-	-	-
	AC M/L 2.835 Liters	-	-	-	-	-	-	-	-
	-	2-CB5 11.355 Liters	4-CB5 22.710 Liters	7CB5 37.854 Liters	-	-	-	-	-
BRITA	-	PURITY C FRESH C50 15.000 Liters	-	-	-	-	-	-	-



Profine® silver

Microfiltration
taste & odour removal



CHARACTERISTICS:

- removes odours and off-tastes
- reduces chlorine
- guarantees a bacteriostatic action
- reduces the organic macromolecules presence

APPLICATIONS



domestic

PROFINE	-	MINI 7.000 Liters	SMALL 15.000 Liters	MEDIUM 24.000 Liters	LARGE 45.000 Liters	-	-	-	-
PENTAIR	-	S-100 5.670 Liters	-	-	-	-	-	-	-
	-	AC M/L 2.835 Liters	-	-	-	-	-	-	-
	-	-	4DC 11.000 Liters	-	-	-	-	-	-
	-	2K PLUS 5.600 Liters	4K PLUS 11.300 Liters	-	-	-	-	-	-
	-	-	-	-	XC2 45.425 Liters	-	-	-	-
	-	-	BH² 11.356 Liters	-	-	-	-	-	-
BRITA	-	-	PURITY C 1000 AC 10.000 Liters	-	-	-	-	-	-



Profine® gold

Ultrafiltration for
drinking water



CHARACTERISTICS:

- removes odours and off-tastes
- reduces chlorine
- prevents passage of 99.9999% of bacteria
- reduces the organic macromolecules presence

APPLICATIONS



domestic

<u>PROFINE</u>	-	SMALL 7.000 Liters	MEDIUM 10.000 Liters	LARGE 15.000 Liters	-	-	-	-	-
<u>PENTAIR</u>	-	-	-	MC2 M/L 34.068 Liters	-	-	-	-	-
	-	AC2 5.678 Liters	-	-	-	-	-	-	-
	-	-	Microguard PRO 2 8.330 Liters	Microguard PRO 4 13.600 Liters	-	-	-	-	-



Profine® ice

Brighting ice with bacteriostatic dechlorative action and limescale reduction



CHARACTERISTICS:

- limescale protection and brilliant ice
- removes odours, off-tastes and chlorine
- bacteriostatic action

APPLICATIONS



PROFINE	MINI 6.000 Liters	SMALL 10.000 Liters	MEDIUM 22.000 Liters	LARGE 30.000 Liters	-	-	-	-	-
PENTAIR	OCS2 5.678 Liters	-	-	-	-	-	-	-	-
	-	4H M/L 11.350 Liters	-	MH2 M/L 34.068 Liters	-	-	-	-	-
	-	6 PK 2CB5-S 11.356 Liters	4-CB5S 22.710 Liters	6 PK 7CB5-S 37.854 Liters	-	-	-	-	-
	2CLM-S 3.785 Liters	-	-	INSURICE i2000² 34.000 Liters	INSURICE i4000² 45.000 Liters	-	-	-	-
	-	BH² 11.356 Liters	-	-	-	-	-	-	-



NOTE

BY-PASS



EASY Bypass Setting

- Very good readability of the display.
- Simple, safe blending adjustment.

0 > 3%

1 > 8%

2 > 30%

3 > 50%

Values refer to flowrate of 1 L/min.

Bestmax SMART



